

GENERATING SET GE 15000 SC - SXC - SXC EAS



- Air cooled diesel engine
- Engine protection (oil pressure/temperature)
- Three-phase asynchronous alternator
- Suitable for electronic equipment
- Ground Fault Interrupter protection
- Trailer (optional)
- Complies with EEC directives
- Prewired for use with Automatic transfer unit (SXC EAS)

Standard equipment											
	Diesel engine	Air cooling	Electric starter	Battery 12V	Battery charger indicator	Hour counter	Engine protection	Oil pressure indicator	Low fuel indicator	Engine temperature	Central lifting eye
Options on request											
	Asynchronous alternator	Voltmeter	Ground fault interrupter	Socket 400V EEC	Socket 230V EEC	Thermal shut off					

- | | | |
|--|--|--|
| Options on request
<ul style="list-style-type: none"> ● Plug 400V 32A 3PNT (T) ● Plug 230V 32A 2PT (M) | <ul style="list-style-type: none"> ● Automatic transfer unit EAS22 ● Remote control TCM22 with cable 10 m ● Earthing kit MT10 | <ul style="list-style-type: none"> ● Site tow CTL400 ● Road tow CTV3 |
|--|--|--|

Technical data	GE 15000 SC	GE 15000 SXC	GE 15000 SXC EAS
----------------	-------------	--------------	------------------

A.C. GENERATION	50 Hz, asynchronous, three-phase, self-excited, self-regulated, brushless		
Three-phase generation	15 kVA (12 kW) / 400 V / 21.7A		
Single-phase generation	10 kVA / 230 V / 43.5 A		
Duty cycle	100%		
Power factor (cos φ)	0.8		
Insulating class	H		

ENGINE	Diesel, 4-stroke, air cooled		
Type	Lombardini 9LD625/2		
Output *	19.1 kW (26 HP)		
Speed	3000 rpm		
Displacement	1250 cm ³		
Cylinders	2		
Fuel consumption	250 g/kWh		

* Maximum output according to ISO 3046/1

GENERAL SPECIFICATIONS			
Tank capacity	26 l		
Running time (Load 75%)	8 h		
Protection	IP 23		
Dimensions Lxwxh (mm)*	1455x870x880		
Weight *	386 kg	406 kg	406 kg
Noise level**	100 LWA (75 dB(A) - 7 m)	96 LWA (71 dB(A) - 7 m)	96 LWA (71 dB(A) - 7 m)

* Dimensions and weight are inclusive of all parts without wheels and towbar ** LWA conforms to EEC Directive 536

Values shown are nominal values. For further information please contact the sales department.