

## GENERATING SET GE 14000 LD/GS EAS



- Engine Diesel - 3000 rpm.
- Air Cooled
- Three-phase 15 kVA - synchronous alternator
- Protections: G.F.I.
- Wrap around protective frame
- Prepared for connection to automatic transfer unit
- ECC sockets: 1x400V/32A 3P+N+T - 1x230V/32A 2P+T - 1x230V/16A 2P+T (schuko)

Standard equipment										
	Diesel engine	Air cooling	Electric Starter	Battery 12V	Battery charger indicator	Hour counter	Oil pressure shut down			
	Synchronous alternator	Voltmeter	Ground fault interrupter	Circuit breaker	EEC sockets	Ready for EAS/TCM				

### Options on request

- Plugs
- Automatic transfer unit EAS15D-806
- Trolley CTM14
- Earthing Kit MT10

### Technical data

### GE 14000 LD/GS EAS

<b>A.C. GENERATION</b>	<b>50 Hz, synchronous, three-phase, self-excited, self-regulated, brushless</b>
Three-phase generation (stand-by)	15 kVA (12 kW) / 400 V / 21.7 A
Three-phase generation (P.R.P.)	13.5 kVA (10.8 kW) / 400 V / 19.5 A
Single-phase generation	5 kVA / 230 V / 21.7 A
Cos φ	0.8
Insulating class	H
Output power to ISO 8528/1	

<b>ENGINE</b>	<b>Diesel, 4-stroke, air cooled</b>
Type	Lombardini 12 LD 477.2
Power (stand-by) *	14.9 kW (20.3 HP)
Power (P.R.P.) *	13.5 kW (18.4 HP)
Speed	3000 rpm
Displacement	454 cm <sup>3</sup>
Cylindres	3
Fuel consumption (75% P.R.P.)	2.8 l/h
* Maximum output according to ISO 3046/1	

<b>GENERAL SPECIFICATIONS</b>	
Tank capacity	18 l
Running time (Load 75%)	5.5 h
Protection	IP 23
Dimensions* LxIhx (mm)	1000x610x750
Weight*	191 kg
Acoustic power	105 LWA (80 dB(A) - 7 m)
* Dimensions and weight are inclusive of all parts without wheels and towbar	

Values shown are nominal values. For further information please contact the sales department.