

GENERATING SET GE 2500 FAMILY



- HONDA, gasoline engine
- Engine shut down (oil)
- Single-phase synchronous alternator
- Protection: overload thermal shut off
- Battery charger 12V - 10A
- Protective frame
- Silenced
- Portable
- Complies with all EEC safety and noise directives

Standard equipment 										
	Gasoline engine	Air cooling	Manual recoil	Engine shut down (oil)						
	Synchronous alternator	Thermal shut off	Socket 230V Schuko	Battery charger	Fuse					

Options on request

● Plug 230V 16A 2PT (M) SCHUKO

● Earthing Kit MT10

Technical Data

GE 2500 FAMILY

A.C. GENERATION	50 Hz, synchronous, single-phase, self-excited, self-regulated, brushless
Single-phase generation (max)	2.3 kVA / 230V / 10 A
Single-phase generation (continuous)	2 kVA / 230V / 8.7 A
Battery charger d.c.	12V - 10A
Duty cycle	100%
Power factor (Cos φ)	1
Insulation class	H
ENGINE	Gasoline, 4-stroke, air cooled
Type	Honda GC160
Output*	3.3 kW (4.5 HP)
Speed	3000 rpm
Displacement	160 cm ³
Cylinders	1
Fuel consumption	313 g/kWh
* Maximum output according to ISO 3046/1	
GENERAL SPECIFICATIONS	
Tank capacity	2 l
Running time (Load 75%)	2.6 h
Protection	IP 21
Dimensions Lxwxh (mm)	555x370x390
Weight	29 kg
Noise level	97 LWA (72 dB(A) - 7 m)

Values shown are nominal values. For further information please contact the sales department.