

GENERATING SET GE 6000 LBS



- Lombardini OHC, Gasoline engine
- Oil alarm shut off
- Single-phase synchronous alternator
- Manual recoil
- Protective frame
- Trolley CTM (optional)
- Meets EEC directives

Standard equipment 										
	Gasoline engine	Air cooling	Manual recoil	Engine shut down (oil)	Oil alert					
	Synchronous alternator	Socket 230V EEC	Thermal shut off							

Options on request

- Plug 230V 16A 2PT (M)

- Earthing kit MT10
- Trolley CTM6000

Technical Data

GE 6000 LBS

A.C. GENERATION	50 Hz, synchronous, single-phase, self-excited, self-regulated, brushless
Single-phase generation	6 kVA (5.4 kW) / 230 V / 26.1 A
Duty cycle	100%
Power factor (Cos φ)	0.9
Insulation class	H
On request other voltages and frequencies (60 Hz)	
ENGINE	Gasoline, 4-stroke, air cooled
Type	Lombardini LGA 340
Output*	6.9 kW (9.4 HP)
Speed	3000 rpm
Displacement	338 cm ³
Cylinders	1
Fuel consumption	342 g/kWh
* Maximum output according to ISO 3046/1	
GENERAL SPECIFICATIONS	
Tank capacity	6 l
Runnig time (Load 75%)	3.7 h
Protection	IP 23
Dimensions Lxwxh (mm)	785x450x550
Weight	65 kg
Noise level **	99 LWA (74 dB(A) - 7 m)
** LWA conforms to EEC Directive 536	

Values shown are nominal values. For further information please contact the sales department.