ISO 9001:2000 - Cert. 0192

GENERATING SET
GE 7000 BS/GS

- Honda OHV petrol engine
- Engine shut down for low oil level
- Single-Phase synchronous alternator
- Output sockets: 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
- Output sockets: 230V / 115V CTE VERSION : 1 x 230V 32A 2P+T CEE
  1 x 115V 32A 2P+T CEE - 1 x 115V 16A 2P+T CEE
- ELCB-GFI (Ground Fault Interruptor)
- Circuit breaker
- Suitable for electronic equipments
- Wrap around protective frame
- Meets EC directives

Standard Equipment

Petrol engine	Air cooling	Manual recoil	Engine shut down (oil)	Hour-meter					* Only 230V/115V Version
GS Synchronous alternator	1~ Sockets	D ELCB-GFI	MT Circuit breaker	T Thermal shut off	V Voltmeter	230V 115V 115V-230V selector			

Options on request

- 230V plug
- 115V plug
- Earthing kit
- Exhaust extension
- Trolley CTM200

Versions on request

- 230V/115V CTE

Technical Data — GE 7000 BS/GS

A.C GENERATION – 50 Hz	**Single-phase synchronous alternator,self-excited, self-regulated, brushless**
*** Stand-by single-phase power (230V)**	6.7 kVA (6 kW) / 230 V / 29.1 A
*** P.R.P. single-phase power (230V)**	5.5 kVA (5 kW) / 230 V / 23.9 A
**** Stand-by single-phase power (115V)**	6.7 kVA (6 kW) / 115 V / 58.2 A
**** P.R.P. single-phase power (115V)**	5.5 kVA (5 kW) / 115 V / 47.8 A
Cos φ	0.9
Insulation class	H

* Output powers according to ISO 8528-1 - ** Only 230V/115V Version

ENGINE	**4-stroke petrol, air cooled, OHV**
Model	Honda GX 390
*** Stand-By net power**	7.7 kW (10.5 HP)
*** P.R.P. net power**	6 kW (8.1 HP)
Cylinders/ Displacement	1/ 389 cm^3
Speed	3000 rpm
Fuel consumption (75% of P.R.P.)	2.5 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATION	
Tank capacity	6.1 l
Running time (75% of P.R.P.)	2.5 h
IP protection degree	IP 23
***Dimensions LxWxh (mm)**	910x525x613 mm
***Dry weight**	82 kg
****Measured acoustic power LwA (pressure LpA)**	96 dB(A)(71 dB(A) @ 7m)
****Guaranteed acoustic power LwA (pressure LpA)**	97 dB(A)(72 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department

© MOSA - Viale Europa, 59 - 20090 Cusago (Milano) - Italy -phone +39-0290352.1 - fax + 39-0290390466 **E-mail**: info@mosa.it **Web site**: www.mosa.it