

GENERATING SET GE 15 PSX EAS - GE 15 PSX EAS (AVR)

- Perkins water cooled diesel engine - 1500 rpm
- Closed crankcase ventilation
- ES engine protection
- Three-phase synchronous alternator
- Electronic voltage regulation (AVR)
- Compound voltage regulation
- Output sockets : 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE
1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
- ELCB-GFI (Ground Fault Interruptor)
- Circuit breaker
- Super silenced
- Trailer (option)
- Ready for connection to automatic transfer unit
- Meets EC directives for safety and noise level



Standard Equipment												
Options on request	<ul style="list-style-type: none"> ● 400V plug ● 230V plug ● Earthing kit 				<ul style="list-style-type: none"> ● Automatic transfer unit (AMF) EAS 28-805 ● Remote control TCM40 ● Tank locking cap 				<ul style="list-style-type: none"> ● Site tow CTL22 ● Road trolley CTV1 			
Factory installation options	<ul style="list-style-type: none"> ● Water heater WH 				Version on request <ul style="list-style-type: none"> ● * (AVR) Electronic voltage regulation version ● Schuko sockets version 							

Technical Data

GE 15 PSX EAS

GE 15 PSX EAS (AVR)

A.C GENERATION – 50 Hz	Three-phase synchronous alternator, self-excited, self-regulated, brushless.	Three-phase synchronous alternator, self-excited, self-regulated
* Stand-by three-phase power	16 kVA (12.8 kW) / 400 V / 23.1 A	15 kVA (12 kW) / 400 V / 21.7 A
* P.R.P. three-phase power	15 kVA (12 kW) / 400 V / 21.7 A	13.5 kVA (10.8 kW) / 400 V / 19.5 A
* P.R.P. single-phase power	5 kVA / 230 V / 21.7 A	5 kVA / 230 V / 21.7 A
Cos φ	0.8	0.8
Insulation class	H	H
* Output powers according to ISO 8528-1		

ENGINE 4-stroke diesel, natural aspirated, indirect injection, water cooled

Model	Perkins 403D-15G
* Stand-By net power	13.3 kW (18 HP)
* P.R.P. net power	12 kW (16.3 HP)
Cylinders/ Displacement	3/ 1496 cm ³
Speed	1500 rpm
Fuel consumption (75% of P.R.P.)	2.8 l/h
* Powers according to ISO 3046-1	

GENERAL SPECIFICATION

Tank capacity	60 l
Running time (75% of P.R.P.)	21.5 h
IP protection degree	IP 23
*Dimensions LxWxh (mm)	1700x950x1080
*Dry weight	540 kg
**Measured acoustic power LwA (pressure LpA)	89 dB(A) (64 dB(A) @ 7 m)
**Guaranteed acoustic power LwA (pressure LpA)	90 dB(A) (65 dB(A) @ 7 m)
* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC	

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.