

GENERATING SET GE 165 PS EAS - GE 165 PMS EAS GE 165 PSX EAS - GE 165 PMSX EAS

- PERKINS water cooled diesel engine - 1500 rpm
- Common-rail engine with electronic governor
- EP6 engine protection
- GE 145 PS/PSX – STAMFORD three-phase synchronous alternator
- GE 145 PMS/PMSX – MARELLI three-phase synchronous alternator
- Four pole circuit breaker
- Oil drain pump
- Bunded base
- Ready for connection to automatic transfer unit
- Meets EC directives for safety and noise level



Standard Equipment											
	Diesel engine	Water cooling	Battery 12V	Fuel level gauge	Engine protection	Electric Starter	low press. shut down	high water shut down	over speed shut down	low fuel shut down	battery charge alarm
Factory installation options											
	Synchronous alternator	Automatic Voltage Regulator	Circuit Breaker	Terminal block	Ammeter	Voltmeter phase selector	Emergency stop button	Siren	Ready for EAS/TCM	Central lifting eye	Cold start aid
	<ul style="list-style-type: none"> Electrical panel with sockets :1x400V 125A 3P+N+T CEE - 1x400V 63A 3P+N+T CEE - 1x400V 32A 3P+N+T CEE - 1x400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE The electrical panel requires an electrical protection : ELR-Earth Leakage Relay (GFI) or Isometer (Insulation monitors) 50/60 Hz Selector Earth Leakage Relay Isometer (Insulation monitors) Radio-control Permanent Magnet Generator 	<ul style="list-style-type: none"> Volt and Hz adjustable from control panel Gauges – water temperature and oil pressure Water heater WH Automatic fuel transfer pump (delivered loose) 	<ul style="list-style-type: none"> Fuel tank 120l Fuel tank 350l 3-way valve fuel system with quick connection for external fuel tank supply 								
Options on request	<ul style="list-style-type: none"> 400 plugs 230 plugs 	<ul style="list-style-type: none"> Automatic transfer unit (AMF) EAS 170-805 Remote control TCM35 	<ul style="list-style-type: none"> Earthing kit 	Version on request	<ul style="list-style-type: none"> 24 h autonomy version 						

Technical Data

GE 165 PS/PMS EAS GE 165 PSX/PMSX EAS

A.C GENERATION – 50 Hz	Three-phase synchronous alternator, self-excited, self-regulated, brushless
* Stand-by three-phase power	165 kVA (132 kW) / 400 V / 238.1 A
* P.R.P. three-phase power	150 kVA (120 kW) / 400 V / 216.5 A
* P.R.P. single-phase power	55 kVA / 230 V / 239.1 A
Cos φ	0.8
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE

Model	PERKINS 1106C-E66TAG3
* Stand-By net power	143.9 kW (195.7 HP)
* P.R.P. net power	129.5 kW (176.1 HP)
Cylinders/ Displacement	6/ 6.6 l (6600 cm ³)
Speed	1500 rpm.
Fuel consumption (75% of P.R.P.)	25.8 l/h

* Powers according to ISO 3046-1

GENERAL SPECIFICATION

Tank capacity	230 l
Running time (75% of P.R.P.)	9 h
IP protection degree	IP 44
*Dimensions LxWxh (mm)	3000x1200x1800
*Dry weight	2160 kg
**Measured acoustic power LwA (pressure LpA)	96 dB(A) (71 dB(A) @ 7 m)
**Guaranteed acoustic power LwA (pressure LpA)	97 dB(A) (72 dB(A) @ 7 m)

* Dimensions and weight without trolley/trailer. **Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department