

GENERATING SET GE 505 P Skid - S - SX

- Perkins Diesel engine, water-cooled with electronic speed regulation.
- Brushless alternator with electronic voltage regulation (AVR)
- "BRAIN" control panel unit with the following features:
 - Automatic Mains Failure with QEA logic
 - Engine protection - high water temp., low oil press., overspeed, low battery voltage etc.
 - More than 30 selectable alarms
 - Digital display - water temp., oil press., fuel level, battery voltage, engine speed, phase and line voltages, currents,
- Connection to PAC load transfer switch (with QEA logic)
- All versions can be prepared for manual or automatic operation (with QEA logic)



Base equipment unit											
	Diesel engine	Water cooling	Electric starter	Battery 24V (2 x 12V)	Emergency stop button	Synchronous alternator	Electronic voltage regulator	Fuel alarm	Overload and short circ. protection		
	BRAIN Unit	Engine shut down oil	Engine shut down temp.	Engine shut down overspeed	Engine shut down battery charge	Hour counter	Main, gen., battery	Main, generator	Countdown maintenance	Remote starting	
Factory installation	<ul style="list-style-type: none"> ● CE Kit (4 poles circuit breaker + G.F.I.) ● QEA Logic ● Fuel level gauge with alarm 			<ul style="list-style-type: none"> ● Heater Kit ● Fuel charging pump kit ● Low level cooling alarm 			<ul style="list-style-type: none"> ● Semiresidential muffler ● Permanent magnet (PHG) alternator 				
Options on request	<ul style="list-style-type: none"> ● PAC (load transfer switch) 										

Technical data	GE 505 P SKID	GE 505 PS	GE 505 PSX
A.C. GENERATION	50 Hz, three-phase, synchronous alternator, self-excited, self-regulated, brushless		
* Three-phase power (L.T.P.)	500 kVA (400 kW) / 400 V / 722 A		
* Three-phase power (P.R.P.)	450 kVA (360 kW) / 400 V / 650 A		
Power factor (cos φ)	0.8		
Insulating class	H		
* Output according to ISO 8528-1			
ENGINE	Diesel, 4-stroke, water cooled		
Type	PERKINS 2806 CE 16 TAG1		
# Output (L.T.P.)	432 kW		
# Output (P.R.P.)	389 kW		
Speed	1500 rpm		
Displacement	15800 cm ³		
Cylinders	6		
Fuel consumption	212 g/kWh		
# Output according to ISO 3046/1			
GENERAL SPECIFICATIONS			
Tank capacity	900 l	620 l	1050 l
Running time (Load 75%)	12 h	8.5 h	14 h
Protection	IP 20	IP 44	IP 44
Dimensions Lxwxh (mm)*	3546x1275x2242	3500x1800x2785	4530x1840x2715
Weight*	4500 kg	5160 kg	5735 kg
Noise level	N/A	112 LWA (82 dB(A) - 7 m)	99 LWA (74 dB(A) - 7 m)
* Dimensions and weight are inclusive of all parts without wheels and towbar			

Values shown are nominal values. For further information please contact the sales department.