

ENGINE DRIVEN WELDER TS 300 SC - SXC/EL



- Electronic regulation of welding current
- Arc control for cellulose electrodes
- Auxiliary power (10 kVA) available while welding
- Ground fault interrupter protection
- Modern, fuel efficient, diesel engine
- Engine protection (oil pressure/temperature)
- Running gear (optional)
- Meets EEC directives

Standard equipment											
	Diesel engine	Air cooling	Electric starter	Battery 12V	Battery charger indicator	Hour Meter	Engine protection	Low oil pressure	Low fuel	High oil temperature	Central lifting eye
Options on request											
	Welding current electr. regulation	Arc force	Asynchronous alternator	Voltmeter	Ground fault interrupter	3~ EEC Socket 400V EEC	1 EEC Socket 230V EEC	Fuse	Ready for TC		
Options on request	<ul style="list-style-type: none"> ● Plug 400V 32A 3PNT (T) ● Plug 230V 32A or 16A 2PT (M) ● Plug 110V 32A or 16A 2PT (M) 			<ul style="list-style-type: none"> ● Welding cables K400 (20+15m, 50mm²) ● Remote control TC2 with cable 20m ● Remote control TC2/50 with cable 50m 				<ul style="list-style-type: none"> ● Trolley CTM300 ● Site tow CTL300 ● Road tow CTV3 ● Earthing kit MT10 			

- Version on request**
- Engine protection and economizer EP1 (Auto Idle), only for SX version
 - Other voltage and frequencies (60 Hz)

Technical data	TS 300 SC/EL	TS 300 SXC/EL
----------------	--------------	---------------

D.C. WELDING		
Current range, continuous	20 - 300 A	
Open circuit voltage	70 V	
Duty cycle	300 A - 60%, 250 A - 100%	
Electrode diameter	2 - 6 mm	
A.C. GENERATION		
50 Hz, asynchronous, three-phase, self-excited, self-regulated, brushless		
Three-phase generation	10 kVA / 400 V / 14.4 A	
Single-phase generation	5 kVA / 230 V / 21.7 A	
Single-phase generation (option)	2.5 kVA / 110 V / 22.7 A	
Single-phase generation (option)	5 kVA / 48 V / 104 A	
Duty cycle	100%	
Insulating class	H	
ENGINE		
Diesel, 4-stroke, air cooled		
Type	Ruggerini RD 210	
Output *	14 kW (19 HP)	
Speed	3000 rpm	
Displacement	954 cm ³	
Cylinders	2	
Fuel consumption	250 g/kWh	
* Maximum output (not overloadable) according to ISO 3046/1		
GENERAL SPECIFICATIONS		
Tank capacity	23 l	
Running time (at duty cycle 60%)	9 h	
Protection	IP 23	
Dimensions * Lxwxh (mm)	1320x790x750	
Weight *	350 kg	370 kg
Noise level	99 LWA (74 dB(A) - 7 m)	93 LWA (68 dB(A) - 7 m)
* Dimensions and weight are inclusive of all parts without wheels and towbar		

Values shown are nominal values. For further information please contact the sales department.